

Thermakraft™

WATERGATE PLUS

Safety Data Sheet

1. Product and Company Identification

Product	Watergate Plus Wall Underlay
Supplier	Thermakraft Limited or Thermakraft Australia Pty Limited

Supplier:	Supplier Address:	Supplier Contact:
Thermakraft Limited	Thermakraft Limited 11 Turin Place East Tamaki Auckland, 2013 New Zealand	Phone: +64 9 2733727 or 0800 806 595 Email: info@thermakraft.co.nz
Thermakraft Australia Pty Limited	Thermakraft Australia Unit 1 No 1 Bungaleen Court Dandenong South Victoria, 3175 Australia	Phone: +61 03 98705880 or 1800 960 338 Email: sales@thermakraft.com.au

2. Composition

- Polypropylene
- Polyethylene
- Calcium carbonate
- Proprietary UV additive
- Proprietary fire retardant additive

Inhalation: Remove to fresh air, seek medical attention if required.

Ingestion: In the unlikely event of ingestion, seek medical attention.

Note: Always read and follow the Thermakraft Datasheet and Installation Guide and use within the intended scope.

3. Hazards Identification

This product is not classified as hazardous under normal use in construction as a wall underlay/wall wrap.

4. First Aid Measures

Skin Contact: The product is an inert solid. In normal use, it is not skin irritating. Seek medical attention if irritation occurs. Molten material will adhere to skin and cause burns, cool material under running water and seek medical attention for removal and to treat burn.

Eye Contact: The product is an inert solid, rinse with water if contact with eyes occur. If irritation occurs, seek medical attention.

5. Fire Fighting Measures

Means of Extinction: Foam, CO₂, dry chemical, water.

Combustion products: Oxides of carbon and nitrogen, hydrogen chloride, aldehydes. Traces of other toxic gases may also be present.

Hazards: Dense toxic smoke – breathing apparatus required and protective clothing required. Excessive dripping and accumulation of molten material can cause burns and spread fire.

6. Handling and Storage

Handling: This product is not classified as hazardous under normal use in construction. Safe lifting practices should be used.

Safety Data Sheet (Cont.)

THERMAKRAFT WATERGATE PLUS

Storage: Store rolls in dry environment away from ultraviolet light exposure. If product is stacked on a pallet, ensure adequate restraints are in place to prevent collapse.

7. Physical and Chemical Properties

Physical State: Solid

Appearance: White nonwoven fabric with printing.

Melting point: Not determined.

8. Stability and Reactivity

Stability: Stable under normal conditions. No further information available.

Reactivity: Can react with strong oxidizing agents and open flames.

9. Ecological Information

Hazards: Not determined.

10. Disposal Considerations

Methods: As per local authority requirements.

11. Transport Information

Methods: No special requirements needed.

12. Other Information

Regulatory information: Check local regulations before use.

The information contained in this Safety Data Sheet corresponds to our level of knowledge at time of publication. It is intended for use by persons at their own risk. The information here only relates to the specific material detailed and does not relate to the combination of the material with any others or with any other processes. Please consult product data sheet and installation guide before use.



0800 806 595
www.thermakraft.co.nz

Thermakraft and Ausmesh products are brought to you by Kingspan Insulation Pty Limited.

