



**Thermakraft™**  
**ONE WRAP**  
**SYSTEM**

10 Products - One system  
One warranty

## Product Data Sheet

# WATERGATE PLUS

### New Zealand's premium all-purpose, fire retardant wall wrap.

Watergate Plus is specifically designed as a wall underlay behind exterior wall cladding. Made from synthetic materials Watergate Plus is fire retardant, water resistant and vapour permeable. The water vapour transfer rate of the product has been optimised to minimise condensation risk in homes without compromising its primary water barrier properties.

Watergate Plus is part of the Thermakraft One Wrap System. Its unique construction allows for easier installation while maintaining best in class performance qualities.

Smarter products. Better buildings.  
**thermakraft.co.nz**



# Watergate Plus

## Premium Synthetic Wall Wrap

Watergate Plus comes in five roll sizes and two soffit roll sizes:

Roll Dimensions			
Product Code	Width	Length	Coverage
WGP1370025	1370mm wide	18.5m long	25m <sup>2</sup> coverage*
WGP1370050	1370mm wide	37.0m long	50m <sup>2</sup> coverage*
WGP1370100	1370mm wide	73.0m long	100m <sup>2</sup> coverage*
WGP2740050	2740mm wide	18.5m long	50m <sup>2</sup> coverage*
WGP2740100	2740mm wide	36.5m long	100m <sup>2</sup> coverage*

Soffit Roll Dimensions			
Product Code	Width	Length	Coverage
WGP600025SOF	685mm wide	36.5m long	25m <sup>2</sup> coverage*
WGP600050SOF	685mm wide	73.0m long	50m <sup>2</sup> coverage*

Custom Branding Available – Contact your Thermakraft Representative for more details

\* **Note:** m<sup>2</sup> is the roll size. For actual coverage, allow for laps and joins.

### Product Description

Watergate Plus is a two-layer laminated wall underlay combining a Polyester non-woven layer with a high quality vapour permeable film. This allows water vapour to pass through from inside the wall cavity whilst water from the exterior is kept out.

The product is simply fixed to timber framing using construction staples and is made to stretch around corners providing a tight fit and reducing the risk of staple tear. It will provide temporary weather protection during construction. (Max 90 Days).

### Scope of Use

Watergate Plus can be used as a wall underlay on both residential and commercial buildings within the following scope:

- With absorbent wall claddings (e.g. timber, brick or fibre cement) or non-absorbent wall claddings (e.g. metal or plastic).
- Can be used with timber and steel framing, either directly fixed or in conjunction with an 18mm minimum drained cavity.
- With masonry veneer in accordance with NZBC Acceptable Solution E2/AS1 and E2/AS4.
- Situated in NZS3604 and NASH Building Wind Zones up to (and including) 'Very High' when used as a standalone flexible underlay, and "Extra High" when used as a flexible underlay over a rigid wall underlay.
- Is suitable as an air barrier in unlined wall spaces.

- Is suitable to be used in conjunction with thermal breaks on steel framed buildings.
- Refer to BRANZ Appraisal No 695 (2017) and CodeMark Certificate BRANZ-CM-1002 for full details.

### General

- Fire retardant.
- Unaffected by LOSP or other solvent based treated timber. However, LOSP or other solvent based treated timber must have sufficient time for the solvent to flash off in a well ventilated area. Recommended minimum 7 days.

### Limitations

- Must NOT be used as a roof underlay.
- Must NOT be exposed to the weather or UV for more than 90 days.
- Watergate Plus is NOT a vapour barrier.

### Compliance

- Watergate Plus has been appraised with the scope limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1 and E2/AS4, with regards to building height and floor plan area.
- Watergate Plus has also been BRANZ appraised for use on buildings subject to specific weathertightness design. Building designers are responsible for the building design and for the incorporation of Watergate Plus into their design in accordance with the declared properties and the instructions of Thermakraft Ltd.

# Watergate Plus

## Premium Synthetic Wall Wrap

### Flammability Index

Thermakraft Watergate Plus Wall Underlay has an AS 1530 Part 2 Flammability Index of not greater than 5 and therefore meets the requirements of NZBC Acceptable Solutions C/AS2, Paragraph 4.17.8 b), for the surface finish requirements of suspended flexible fabric used as an underlay to exterior cladding that is exposed to view in occupied spaces.

### Durability

Meets the Performance Requirements of NZBC Clauses B2, Durability (B2.3.1 (a) 50 years, B2.3.1 (b) 15 years and B2.3.2), E2 External Moisture (E2.3.2), and F2 Hazardous Building Materials F2.3.1, providing:

- It is not damaged.
- Installed in accordance with instruction guide.
- Is not left exposed for more than 90 days.
- Installed by or under guidance of Licensed Building Practitioners.
- Is compatible with cladding system used.\*

\* **Note:** specifiers and product user must confirm wall cladding system compatibility with the underlay before installation.

### Product Warranty

Standard Thermakraft warranty applies. Refer to Thermakraft Warranty Statement for further details. This is available online at [thermakraft.co.nz](http://thermakraft.co.nz) or call **0800 806 595**.

### Property Performance

NZBC E2/AS1 Table 23 (NZS2295) Wall Underlay Properties	Absorbency	Vapour Resistance	pH of Extract	Shrinkage	Water Resistance	Air Resistance
Property Performance Requirement	≥ 100gsm	≤ 7 MN.s/g	≥ 6 and ≤ 9	≤ 0.5%	≥ 20mm	≥ 0.1 MN.s/m <sup>3</sup>
Property Performance	Pass	Pass	Pass	Pass	Pass	Can be used as an air barrier

Thermakraft Limited / 0800 806 595

Smarter products. Better buildings.  
**thermakraft.co.nz**



The recommendations contained in Thermakraft's literature are based on good building practice, but are not an exhaustive statement of all relevant information and are subject to any conditions contained in the Warranty. All product dimensions and performance claims are subject to any variation caused by normal manufacturing process and tolerances. Furthermore, as the successful performance of the relevant system depends on numerous factors outside the control of Thermakraft (for example quality of workmanship and design), Thermakraft shall not be liable for the recommendations in that literature and the performance of the Product, including its suitability for any purpose or ability to satisfy the relevant provisions of the Building Code, regulations and standards. Literature subject to change without notification. Latest documentation can be found on the website. E&OE.